




## Display 1001



Display	1001
Product number	251 007 020
<b>Mechanical Data</b>	
Dimension diameter / depth (mm)	Ø 60 / 50
Degree of protection	IP65
Temperature range	-20 °C - +70 °C -4 °F - +158 °F
Weight	63 g
Mounting (mm)	Mounting hole Ø 53
<b>Electrical Data</b>	
DC power supply	9 V - 60 V
Power input @ 24 V	≤ 100 mA
Memory: Program / Configuration / Data	96 kB / 65 kB / 3.3 kB
Indicator LEDs	3 (default symbols: maintenance, caution, battery)
Keys (backlit)	3
Buzzer	1
<b>Display Data</b>	
Display type	2 x 8 characters LCD with backlight
<b>Interfaces / Protocols</b>	
CAN (ISO 11898-2 High Speed, 2.0 B)	1
CANopen, Layer 2, J1939	✓
<b>Software</b>	
Proemion Tools CD	157 002 059
<b>Product number / Accessories</b>	
Rounded seal o-ring Display 1001	140 700 003
Mounting kit (brackets)	141 000 011
CAN cable M12 5-pin / D-Sub + power	136 000 028
CAN bus terminator D-Sub / D-Sub	157 000 033
<b>Starter Kit</b>	
Display 1001 Starter Kit	253 000 047
<b>Certifications</b>	
CE, FCC, E1	✓